



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/018,752	03/13/2002	Yohei Kawabata	2001_1871A	2619

513 7590 07/25/2007
WENDEROTH, LIND & PONACK, L.L.P.
2033 K STREET N. W.
SUITE 800
WASHINGTON, DC 20006-1021

EXAMINER

AILES, BENJAMIN A

ART UNIT	PAPER NUMBER
----------	--------------

2142

MAIL DATE	DELIVERY MODE
-----------	---------------

07/25/2007

PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Office Action Summary

Application No.

10/018,752

Applicant(s)

KAWABATA ET AL.

Examiner

Benjamin A. Ailes

Art Unit

2142

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 26 April 2007.
- 2a) ☒ This action is **FINAL**. 2b) ☐ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 10-16 is/are pending in the application.
- 4a) Of the above claim(s) _____ is/are withdrawn from consideration.
- 5) ☐ Claim(s) _____ is/are allowed.
- 6) ☒ Claim(s) 10-16 is/are rejected.
- 7) ☐ Claim(s) _____ is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on _____ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All b) ☐ Some * c) ☐ None of:
- ☐ Certified copies of the priority documents have been received.
 - ☐ Certified copies of the priority documents have been received in Application No. _____.
 - ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

* See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- | | |
|--|---|
| 1) <input type="checkbox"/> Notice of References Cited (PTO-892) | 4) <input type="checkbox"/> Interview Summary (PTO-413)
Paper No(s)/Mail Date. _____ |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948) | 5) <input type="checkbox"/> Notice of Informal Patent Application |
| 3) <input type="checkbox"/> Information Disclosure Statement(s) (PTO/SB/08)
Paper No(s)/Mail Date _____ | 6) <input type="checkbox"/> Other: _____ |

DETAILED ACTION

1. This action is in response to correspondence filed 26 April 2007.
2. Claims 10-16 remain pending.

Claim Rejections - 35 USC § 112

3. The following is a quotation of the second paragraph of 35 U.S.C. 112:

The specification shall conclude with one or more claims particularly pointing out and distinctly claiming the subject matter which the applicant regards as his invention.

4. Claims 11 and 15 are rejected under 35 U.S.C. 112, second paragraph, as being indefinite for failing to particularly point out and distinctly claim the subject matter which applicant regards as the invention.

5. Regarding claim 11, claim 11 recites in line 18: "a system time clock/program clock reference rate ratio calculator..." Based on the use of a forward slash (/), it is unclear what is required by the claim limitation. Specifically, it is unclear if the claim is to be read (a) "a system time clock and program clock reference rate ratio calculator..." OR (b) "a system time clock or program clock reference rate ratio calculator..." For examination purposes, the claim will be read as option (b), in the alternative form.

Appropriate correction is required.

6. Regarding claim 15, claim 15 recites in line 14: "a system time clock/program clock reference rate ratio calculator..." Based on the use of a forward slash (/), it is unclear what is required by the claim limitation. Specifically, it is unclear if the claim is to be read (a) "a system time clock and program clock reference rate ratio calculator..." OR (b) "a system time clock or

Art Unit: 2142

program clock reference rate ration calculator..." For examination purposes, the claim will be read as option (b), in the alternative form.

7. Appropriate correction is required.

Claim Rejections - 35 USC § 103

8. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

9. This application currently names joint inventors. In considering patentability of the claims under 35 U.S.C. 103(a), the examiner presumes that the subject matter of the various claims was commonly owned at the time any inventions covered therein were made absent any evidence to the contrary. Applicant is advised of the obligation under 37 CFR 1.56 to point out the inventor and invention dates of each claim that was not commonly owned at the time a later invention was made in order for the examiner to consider the applicability of 35 U.S.C. 103(c) and potential 35 U.S.C. 102(e), (f) or (g) prior art under 35 U.S.C. 103(a).

10. Claims 10-16 are rejected under 35 U.S.C. 103(a) as being unpatentable over Hemkumar et al. (US 6,356,871 B1), hereinafter referred to as Hemkumar, in view of Olin (US 6,708,220 B1).

11. Regarding claim 10, Hemkumar teaches a storage-type data broadcast system for transmitting a first transport stream constituting at least one content

Art Unit: 2142

and containing a plurality of packet data having a program clock reference as reference clock information when reproducing the content, at a second transfer rate different from a first transfer rate which is determined by the reference clock information, and extracting the plurality of packet data composing the content from the transmitted first transport stream to generate and store a second transport stream, the data broadcast service system comprising:

a transmitter for transmitting the first transport stream of the plurality of packet data composing the content at the second transfer rate (col. 12, lines 17-23).

Hemkumar teaches a receiver for receiving the transmitted first transport stream (col. 12, lines 24-29) but does not explicitly teach detecting a transfer rate ratio between the first transfer rate and the second transfer rate to generate the second transport stream based on the detected transfer rate ratio. However, in related art, Olin teaches on this aspect wherein Olin teaches a method for automatically adjusting transfer rates wherein a server monitors and records the transfer of selected data sets and therefore teaches on the detection of preferred transfer rate ratios (col. 6, ll. 28-37). One of ordinary skill in the art at the time of the applicant's invention would have found it obvious to combine the teachings of Hemkumar with the teachings of Olin. One of ordinary skill in the art would have been motivated to make such a combination as taught by Olin wherein it is advantageous to utilize optimum levels of transfer rates regardless of network/modem speed, server, and other system characteristics (Olin, col. 6, ll. 34-37). Hemkumar and Olin teach the receiver comprising: a program clock

Art Unit: 2142

reference extractor for extracting the program clock reference contained in the first transport stream ((Hemkumar, col. 12, lines 30-32), a system time clock recoverer for recovering, based on the extracted program clock reference, a system time clock which is a processing reference clock for the packet data (Hemkumar, col. 12, ll. 30-44), a program clock reference correction factor calculator for detecting the transfer rate ratio based on two contiguous extracted program clock references, and deriving, based on the detected transfer rate ratio, a correction factor for correcting the extracted program clock reference so as to match the second transfer rate (Hemkumar, col. 12, lines 35-38), a program clock reference corrector for correcting the extracted program clock reference based on the derived correction factor (Hemkumar, col. 12, lines 35-38), and wherein said system time clock recoverer is feedback-controlled to recover the system time clock based on the corrected program clock reference (Hemkumar, col. 12, lines 45-52).

12. Regarding claim 11, Hemkumar teaches a storage-type data broadcast system for transmitting a first transport stream constituting at least one content and containing a plurality of packet data having a program clock reference as reference clock information when reproducing the content, at a second transfer rate different from a first transfer rate, which is determined by the reference clock information, and extracting the plurality of packet data composing the content from the transmitted first transport stream to generate and store a second transport stream, the storage-type data broadcast service system comprising:

a transmitter for transmitting the first transport stream of the plurality of packet data composing the content at the second transfer rate (col. 12, lines 17-23).

Hemkumar teaches a receiver for receiving the transmitted first transport stream (col. 12, lines 24-29) but does not explicitly teach detecting a transfer rate ratio between the first transfer rate and the second transfer rate to generate the second transport stream based on the detected transfer rate ratio. However, in related art, Olin teaches on this aspect wherein Olin teaches a method for automatically adjusting transfer rates wherein a server monitors and records the transfer of selected data sets and therefore teaches on the detection of preferred transfer rate ratios (col. 6, ll. 28-37). One of ordinary skill in the art at the time of the applicant's invention would have found it obvious to combine the teachings of Hemkumar with the teachings of Olin. One of ordinary skill in the art would have been motivated to make such a combination as taught by Olin wherein it is advantageous to utilize optimum levels of transfer rates regardless of network/modem speed, server, and other system characteristics (Olin, col. 6, ll. 34-37). Hemkumar and Olin teach the receiver comprising: a program clock reference extractor for extracting the program clock reference contained in the first transport stream ((Hemkumar, col. 12, lines 30-32), a system time clock recoverer for recovering, based on the extracted program clock reference, a system time clock which is a processing reference clock for the packet data (Hemkumar, col. 12, ll. 30-44), a system time clock/program clock reference correction factor calculator for deriving, based on the extracted program clock

Art Unit: 2142

reference and the recovered system time clock, a correction factor for correcting the extracted program clock reference so as to match the second transfer rate (Hemkumar, col. 12, lines 35-38), a program clock reference corrector for correcting the extracted program clock reference based on the correction factor (Hemkumar, col. 12, lines 35-38), and wherein said system time clock recoverer is feedback-controlled to recover the system time clock based on the corrected program clock reference (Hemkumar, col. 12, lines 45-52).

13. Regarding claim 12, Hemkumar teaches a storage-type data broadcast system for transmitting a first transport stream constituting at least one content and containing a plurality of packet data having a program clock reference as reference clock information when reproducing the content, at a second transfer rate different from a first transfer rate, which is determined by the reference clock information, and extracting the plurality of packet data composing the content from the transmitted first transport stream to generate and store a second transport stream, the storage-type data broadcast service system comprising:

a transmitter for transmitting the first transport stream of the plurality of packet data composing the content at the second transfer rate (col. 12, lines 17-23).

Hemkumar teaches a receiver for receiving the transmitted first transport stream (col. 12, lines 24-29) but does not explicitly teach detecting a transfer rate ratio between the first transfer rate and the second transfer rate to generate the second transport stream based on the detected transfer rate ratio. However, in related art, Olin teaches on this aspect wherein Olin teaches a method for

Art Unit: 2142

automatically adjusting transfer rates wherein a server monitors and records the transfer of selected data sets and therefore teaches on the detection of preferred transfer rate ratios (col. 6, ll. 28-37). One of ordinary skill in the art at the time of the applicant's invention would have found it obvious to combine the teachings of Hemkumar with the teachings of Olin. One of ordinary skill in the art would have been motivated to make such a combination as taught by Olin wherein it is advantageous to utilize optimum levels of transfer rates regardless of network/modem speed, server, and other system characteristics (Olin, col. 6, ll. 34-37). Hemkumar and Olin teach the receiver comprising: a program clock reference extractor for extracting the program clock reference contained in the first transport stream ((Hemkumar, col. 12, lines 30-32), a program clock reference specifier for causing said program clock reference extractor to extract, as a standard program clock reference, the program clock reference contained in the first transport stream and contained in packet data transferred at the first transfer rate (Hemkumar, col. 12, ll. 30-44), and a system time clock recoverer for recovering, based on the extracted standard program clock reference, a system time clock which is a processing reference clock for the packet data (Hemkumar, col. 12, lines 35-38).

14. Regarding claim 13, Hemkumar teaches a storage-type data broadcast system for transmitting a first transport stream constituting at least one content and containing a plurality of packet data having a program clock reference as reference clock information when reproducing the content, at a second transfer rate different from a first transfer rate, which is determined by the reference clock

Art Unit: 2142

information, and extracting the plurality of packet data composing the content from the transmitted first transport stream to generate and store a second transport stream, the storage-type data broadcast service system comprising:

a transmitter for transmitting the first transport stream of the plurality of packet data composing the content at the second transfer rate (col. 12, lines 17-23).

Hemkumar teaches a receiver for receiving the transmitted first transport stream (col. 12, lines 24-29) but does not explicitly teach detecting a transfer rate ratio between the first transfer rate and the second transfer rate to generate the second transport stream based on the detected transfer rate ratio. However, in related art, Olin teaches on this aspect wherein Olin teaches a method for automatically adjusting transfer rates wherein a server monitors and records the transfer of selected data sets and therefore teaches on the detection of preferred transfer rate ratios (col. 6, ll. 28-37). One of ordinary skill in the art at the time of the applicant's invention would have found it obvious to combine the teachings of Hemkumar with the teachings of Olin. One of ordinary skill in the art would have been motivated to make such a combination as taught by Olin wherein it is advantageous to utilize optimum levels of transfer rates regardless of network/modem speed, server, and other system characteristics (Olin, col. 6, ll. 34-37). Hemkumar and Olin teach the receiver comprising: a program clock reference extractor for extracting the program clock reference contained in the first transport stream ((Hemkumar, col. 12, lines 30-32), a system time clock recoverer for recovering, based on the extracted program clock reference, a

Art Unit: 2142

system time clock which is a processing reference clock for the packet data (Hemkumar, col. 12, ll. 30-44), a program clock reference correction factor generator for extracting the transfer rate ratio from the first transport stream, and deriving, based on the extracted transfer rate ratio, a correction factor for correcting the extracted program clock reference so as to match the second transfer rate (Hemkumar, col. 12, lines 35-38), a program clock reference corrector for correcting the extracted program clock reference based on the correction factor (Hemkumar, col. 12, lines 35-38), and wherein said system time clock recoverer is feedback-controlled to recover the system time clock based on the corrected program clock reference (Hemkumar, col. 12, lines 45-52).

15. Regarding claim 14, Hemkumar teaches a receiver for receiving a first transport stream constituting at least one content and containing a plurality of packet data having a program clock reference as reference clock information when reproducing the content, at a second transfer rate different from a first transfer rate which is determined by the reference clock information, and extracting the plurality of packet data composing the content from the received first transport stream to generate and store a second transport stream (col. 12, lines 24-29).

Hemkumar teaches a receiver for receiving the transmitted first transport stream (col. 12, lines 24-29) but does not explicitly teach detecting a transfer rate ratio between the first transfer rate and the second transfer rate to generate the second transport stream based on the detected transfer rate ratio. However, in related art, Olin teaches on this aspect wherein Olin teaches a method for

Art Unit: 2142

automatically adjusting transfer rates wherein a server monitors and records the transfer of selected data sets and therefore teaches on the detection of preferred transfer rate ratios (col. 6, ll. 28-37). One of ordinary skill in the art at the time of the applicant's invention would have found it obvious to combine the teachings of Hemkumar with the teachings of Olin. One of ordinary skill in the art would have been motivated to make such a combination as taught by Olin wherein it is advantageous to utilize optimum levels of transfer rates regardless of network/modem speed, server, and other system characteristics (Olin, col. 6, ll. 34-37). Hemkumar and Olin teach the receiver comprising: a program clock reference extractor for extracting the program clock reference contained in the first transport stream (Hemkumar, col. 12, lines 30-32), a system time clock recoverer for recovering, based on the extracted program clock reference, a system time clock which is a processing reference clock for the packet data (Hemkumar, col. 12, ll. 30-44), a program clock reference correction factor calculator for detecting the transfer rate ratio based on two contiguous extracted program clock references, and deriving, based on the detected transfer rate ratio, a correction factor for correcting the extracted program clock reference so as to match the second transfer rate (Hemkumar, col. 12, lines 35-38), a program clock reference corrector for correcting the extracted program clock reference based on the derived correction factor (Hemkumar, col. 12, lines 35-38), and wherein said system time clock recoverer is feedback-controlled to recover the system time clock based on the corrected program clock reference (Hemkumar, col. 12, lines 45-52).

Art Unit: 2142

16. Regarding claim 15, Hemkumar teaches a receiver for receiving a first transport stream constituting at least one content and containing a plurality of packet data having a program clock reference as reference clock information when reproducing the content, at a second transfer rate different from a first transfer rate which is determined by the reference clock information, and extracting the plurality of packet data composing the content from the received first transport stream to generate and store a second transport stream (col. 12, lines 24-29).

Hemkumar teaches a receiver for receiving the transmitted first transport stream (col. 12, lines 24-29) but does not explicitly teach detecting a transfer rate ratio between the first transfer rate and the second transfer rate to generate the second transport stream based on the detected transfer rate ratio. However, in related art, Olin teaches on this aspect wherein Olin teaches a method for automatically adjusting transfer rates wherein a server monitors and records the transfer of selected data sets and therefore teaches on the detection of preferred transfer rate ratios (col. 6, ll. 28-37). One of ordinary skill in the art at the time of the applicant's invention would have found it obvious to combine the teachings of Hemkumar with the teachings of Olin. One of ordinary skill in the art would have been motivated to make such a combination as taught by Olin wherein it is advantageous to utilize optimum levels of transfer rates regardless of network/modem speed, server, and other system characteristics (Olin, col. 6, ll. 34-37). Hemkumar and Olin teach the receiver comprising: a program clock reference extractor for extracting the program clock reference contained in the

Art Unit: 2142

first transport stream (Hemkumar, col. 12, lines 30-32), a system time clock recoverer for recovering, based on the extracted program clock reference, a system time clock which is a processing reference clock for the packet data (Hemkumar, col. 12, ll. 30-44), a system time clock/program clock reference rate ratio calculator for deriving, based on the extracted program clock reference and the recovered system time clock, a correction factor for correcting the extracted program clock reference so as to match the second transfer rate (Hemkumar, col. 12, lines 35-38), a program clock reference corrector for correcting the extracted program clock reference based on the correction factor (Hemkumar, col. 12, lines 35-38), and wherein said system time clock recoverer is feedback-controlled to recover the system time clock based on the corrected program clock reference (Hemkumar, col. 12, lines 45-52).

17. Regarding claim 16, Hemkumar teaches a receiver for receiving a first transport stream constituting at least one content and containing a plurality of packet data having a program clock reference as reference clock information when reproducing the content, at a second transfer rate different from a first transfer rate which is determined by the reference clock information, and extracting the plurality of packet data composing the content from the received first transport stream to generate and store a second transport stream (col. 12, lines 24-29).

Hemkumar teaches a receiver for receiving the transmitted first transport stream (col. 12, lines 24-29) but does not explicitly teach detecting a transfer rate ratio between the first transfer rate and the second transfer rate to generate the

Art Unit: 2142

second transport stream based on the detected transfer rate ratio. However, in related art, Olin teaches on this aspect wherein Olin teaches a method for automatically adjusting transfer rates wherein a server monitors and records the transfer of selected data sets and therefore teaches on the detection of preferred transfer rate ratios (col. 6, ll. 28-37). One of ordinary skill in the art at the time of the applicant's invention would have found it obvious to combine the teachings of Hemkumar with the teachings of Olin. One of ordinary skill in the art would have been motivated to make such a combination as taught by Olin wherein it is advantageous to utilize optimum levels of transfer rates regardless of network/modem speed, server, and other system characteristics (Olin, col. 6, ll. 34-37). Hemkumar and Olin teach the receiver comprising: a program clock reference extractor for extracting the program clock reference contained in the first transport stream (Hemkumar, col. 12, lines 30-32), a program clock reference specifier for causing said program clock reference extractor to extract, as a standard program clock reference, the program clock reference contained in the first transport stream and contained in packet data transferred at the first transfer rate (Hemkumar, col. 12, ll. 30-44), and a system time clock recoverer for recovering, based on the extracted standard program clock reference, a system time clock which is a processing reference clock for the packet data (Hemkumar, col. 12, lines 35-38).

Response to Arguments

18. Applicant's arguments filed 26 April 2007 have been fully considered but they are not persuasive.

Claims 10 and 14

19. Applicant argues that claims 10 and 14 are patentable over the combination of Hemkumar and Olin since claims 10 and 14 recite a storage-type data broadcast service system, including, in part, a receiver having a system time clock recoverer for recovering, based on an extracted program clock reference contained in a first transport stream, a system time clock which is a processing reference clock for packet data; a program clock reference correction factor calculator for detecting a transfer rate ratio between a first transfer rate and a second transfer rate based on two contiguous extracted program clock references, and deriving, based on the detected transfer rate ratio, a correction factor for correcting the extracted program clock reference so as to match the second transfer rate; and a program clock reference corrector for correcting the extracted program clock reference based on the derived correction factor, wherein the system time clock recoverer is feedback-controlled to recover the system time clock based on the corrected program clock reference. Applicant further argues that the claimed storage-type data broadcast service system is capable of recovering the system time clock even when distribution occurs at, for example, a bit stream transfer rate. And finally argues that the combination of Hemkumar and Olin fails to disclose or suggest the above-discussed features of claim 10 that are capable of achieving this effect. Specifically, applicant argues (on page 9, first full paragraph) that Hemkumar fails to disclose or suggest the claimed "system time clock recoverer, program clock reference correction factor calculator, and program clock reference corrector" as recited in claim 10.

Art Unit: 2142

Examiner respectfully disagrees with the applicant. In response to applicant's initial argument, examiner sustains the rejection as outlined above in the rejections with respect to the newly filed claims. In response to applicant's argument that Hemkumar fails to disclose or suggest a "system time clock recover, a program clock reference correction factor calculator, and program clock reference corrector", examiner maintains that Hemkumar teaches on these aspects in column 12. Specifically, Hemkumar teaches on the aspect of a "system time clock recoverer" in lines 24-30 wherein a System Time Clock (STC) is appropriately set and derived from an oscillator and is generated on the decoder end of the system. Hemkumar teaches on the aspect of a "program clock reference correction factor calculator" in lines 35-38 of column 12 wherein a PCR value is calculated wherein synchronization is deemed necessary. Finally, Hemkumar teaches on the aspect of a "program clock reference corrector" in lines 35-38 of column 12 wherein Hemkumar further teaches the need to calculate and synchronize received PCR values by the decoder in order to maintain synchronization. Therefore, with respect to the combination of Hemkumar and Olin, claims 10 and 14 are not deemed patentable.

Claims 11 and 15

20. Applicant argues that claims 11 and 15 are patentable over the combination of Hemkumar and Olin since claims 11 and 15 recite a storage-type data broadcast service system, including, in part, a receiver having a system time clock recoverer for recovering, based on an extracted program clock reference contained in a first transport stream, a system time clock which is a processing

reference clock for packet data; a system time clock/program clock reference rate ratio calculator for deriving, based on the extracted program clock reference and the recovered system time clock, a correction factor for correcting the extracted program clock reference so as to match a second transfer rate; and a program clock reference corrector for correcting the extracted program clock reference based on the correction factor, wherein the system time clock recoverer is feedback- controlled to recover the system time clock based on the corrected program clock reference. And argues further that the combination of Hemkumar and Olin fails to disclose or suggest the above-discussed features of claim 10 that are capable of achieving this effect. Specifically, applicant argues that Hemkumar fails to disclose or suggest the claimed "system time clock recoverer, system time clock/program clock reference rate ratio calculator, and program clock reference corrector" as recited in claim 11. Examiner respectfully disagrees with the applicant. In response to applicant's initial argument, examiner sustains the rejection as outlined above in the rejections with respect to the newly filed claims. In response to applicant's argument that Hemkumar fails to disclose or suggest a "system time clock recoverer, system time clock/program clock reference rate ratio calculator, and program clock reference corrector", examiner maintains that Hemkumar teaches on these aspects in column 12. Specifically, Hemkumar teaches on the aspect of a "system time clock recoverer" in lines 24-30 wherein a System Time Clock (STC) is appropriately set and derived from an oscillator and is generated on the decoder end of the system. Hemkumar teaches on the aspect of a "system time clock/program clock

Art Unit: 2142

reference rate ratio calculator” in lines 35-38 of column 12 wherein a PCR value is calculated wherein synchronization is deemed necessary. Finally, Hemkumar teaches on the aspect of a “program clock reference corrector” in lines 35-38 of column 12 wherein Hemkumar further teaches the need to calculate and synchronize received PCR values by the decoder in order to maintain synchronization. Therefore, with respect to the combination of Hemkumar and Olin, claims 11 and 15 are not deemed patentable.

Claims 12 and 16

Applicant argues that claims 12 and 16 are patentable over the combination of Hemkumar and Olin since claim 12 recites a storage-type data broadcast service system, including, in part, a receiver having a program clock reference extractor for extracting a program clock reference contained in a first transport stream; a program clock reference specifier for causing the program clock reference extractor to extract, as a standard program clock reference, the program clock reference contained in the first transport stream and contained in packet data transferred at a first transfer rate; and a system time clock recoverer for recovering, based on the extracted standard program clock reference, a system time clock which is a processing reference clock for the packet data. Specifically, applicant argues that Hemkumar fails to disclose or suggest the claimed “system time clock recoverer, a program clock reference specifier, and a system time clock recoverer” as recited in claim 12. Examiner respectfully disagrees with the applicant. In response to applicant’s initial argument, examiner sustains the rejection as outlined above in the rejections with respect to the newly filed claims.

Art Unit: 2142

In response to applicant's argument that Hemkumar fails to disclose or suggest a "system time clock recoverer, a program clock reference specifier, and a system time clock recoverer", examiner maintains that Hemkumar teaches on these aspects in column 12. Specifically, Hemkumar teaches on the aspect of a "system time clock recoverer" in lines 24-30 wherein a System Time Clock (STC) is appropriately set and derived from an oscillator and is generated on the decoder end of the system. Hemkumar teaches on the aspect of a "a program clock reference specifier" in lines 35-38 of column 12 wherein a PCR value is calculated wherein synchronization is deemed necessary. Finally, Hemkumar teaches on the aspect of a "a system time clock recoverer" in lines 35-38 of column 12 wherein Hemkumar further teaches the need to calculate and synchronize received PCR values by the decoder in order to maintain synchronization. Therefore, with respect to the combination of Hemkumar and Olin, claims 12 and 16 are not deemed patentable.

Claim 13

Applicant argues that claim 13 is patentable over the combination of Hemkumar and Olin since claim 13 recites a storage-type data broadcast service system, including, in part, a receiver having a system time clock recoverer for recovering, based on an extracted program clock reference contained in a first transport stream, a system time clock which is a processing reference clock for packet data; a program clock reference correction factor generator for extracting the transfer rate ratio from the first transport stream, and deriving, based on the extracted transfer rate ratio, a correction factor for correcting the extracted

Art Unit: 2142

program clock reference so as to match the second transfer rate; and a program clock reference corrector for correcting the extracted program clock reference based on the correction factor, wherein the system time clock recoverer is feedback- controlled to recover the system time clock based on the corrected program clock reference. Specifically, applicant argues that Hemkumar and Olin fail to disclose or suggest the claimed “system time clock recoverer, a program clock reference correction factor generator, and program clock reference corrector” as recited in claim 13. Examiner respectfully disagrees with the applicant. In response to applicant’s initial argument, examiner sustains the rejection as outlined above in the rejections with respect to the newly filed claims. In response to applicant’s argument that Hemkumar fails to disclose or suggest a “system time clock recoverer, a program clock reference correction factor generator, and program clock reference corrector”, examiner maintains that Hemkumar teaches on these aspects in column 12. Specifically, Hemkumar teaches on the aspect of a “system time clock recoverer” in lines 24-30 wherein a System Time Clock (STC) is appropriately set and derived from an oscillator and is generated on the decoder end of the system. Hemkumar teaches on the aspect of a “a program clock reference correction factor generator” in lines 35-38 of column 12 wherein a PCR value is calculated wherein synchronization is deemed necessary. Finally, Hemkumar teaches on the aspect of a “program clock reference corrector” in lines 35-38 of column 12 wherein Hemkumar further teaches the need to calculate and synchronize received PCR values by the decoder in order to maintain synchronization. Therefore, with respect to the

Art Unit: 2142

combination of Hemkumar and Olin, claims 12 and 16 are not deemed patentable.

Conclusion

21. **THIS ACTION IS MADE FINAL.** Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire THREE MONTHS from the mailing date of this action. In the event a first reply is filed within TWO MONTHS of the mailing date of this final action and the advisory action is not mailed until after the end of the THREE-MONTH shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event, however, will the statutory period for reply expire later than SIX MONTHS from the mailing date of this final action.


Any inquiry concerning this communication or earlier communications from the examiner should be directed to Benjamin A. Ailes whose telephone number is (571)272-3899. The examiner can normally be reached on M-F 6:30-4, IFP Work Schedule.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Andrew Caldwell can be reached on (571)272-3868. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Art Unit: 2142

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

baa



ANDREW CALDWELL
SUPERVISORY PATENT EXAMINER